




User Manual

INSTALLATION

Congratulations on your purchase of our product! We hope RECOIL AUDIO Acoustics will delight you with its impressive performance. In producing our speakers, we utilize high-quality components and cutting-edge materials. This manual contains essential instructions for proper system installation and use. Before installation, please carefully review all guidelines provided. Failure to follow these instructions may result in product damage or unintended malfunctions.

SPECIFICATIONS

Configuration: 2-way
Size: 140x192mm (5"x7")
RMS Power : 40 W
Peak Power : 160W
Nominal Resistance (Ohm) : 4 Ω
Minimum Resistance (Ohm) : 3.4 Ω
Sensitivity (1W/M) : 83 dB(+/-3dB)
Frequency Range: 70-20 kHz
Cone Material: Pressed Paper Fiber (Dampproof)
Suspension Material: Nitrile Butadiene Rubber
Voice Coil Diameter: 25.5 mm (1.0")
Coil Material: KSV
Magnet Material : Ferrite



THIELE- SMALL PARAMETERS

Fs: 70 Hz	Sd: 95 cm2
Re: 3.4 ohm	X max: 3.0mm/ 0.12 in
Qes: 1.29	Mms: 11.43g
Qms: 5.97	Bl: 3.66 Tm
Qts: 1.06	No: 0.15%
Vas: 5.65 L/0.2 FT3	CMS: 440.16 uM/N