

POWER FOR THE WAVES
THE PURE MARINE CERTIFIED PRODUCT

HTX 8 M-FL-TW

MARINE TOWER COAX FLAT WHITE

HTX 8 M-FL-TC

MARINE TOWER COAX FLAT BLACK



TECHNICAL SPECIFICATIONS

Component	Two way coaxial	
Size		
Woofers	mm (in.)	200 (8)
Tweeter diaphragm	mm (in.)	36 (1.4)
Voice Coil Ø		
Woofers	mm (in.)	32 (1.26)
Tweeter	mm (in.)	20 (0.8)
Power Handling		
	W peak	200
	W continuous	100
Impedance	Ω	4
Frequency Response	Hz	45 ÷ 25k
Woofers Magnet size D x d x h	mm (in.)	90 x 40 x 20 (3.54 x 1.57 x 0.79)
Tweeter Magnet size D x h	mm (in.)	19,7 x 3 (0.78 x 0.12)
Weight of one speaker	kg (lb.)	5,4 (11.9)
Woofers Magnet	High density flux ferrite	
Tweeter Magnet	Neodymium	
Cone	Polypropylene with UV inhibitors	
Dome	PEI	
Xmech	mm (in.)	±8,5 (0.33)

ELECTRO-ACOUSTIC PARAMETERS

D	mm	174
Xmax	mm	4,5
Re	Ω	3,4
Fs	Hz	51
Le	mH	0,46
Vas	l	26,1
Mms	g	30
Cms	mm/N	0,33
BL	T·m	6,33
Qts		0,78
Qes		0,82
Qms		14,7
Spl	dB	91

1. Hertz **Pure Marine Certified Product** stamp featuring the IP65 protection grade, ASTM-D4329 standards for UV resistance and ASTM-B117 for salt fog operability.
2. Equipped with dedicated 8" coaxial speaker featuring a long-throw 32 mm (1.26") voice coil woofer with polypropylene cone injected with UV inhibitors and 1.4" Neodymium magnet tweeter.
3. RGB led lighting creates sophisticated atmosphere, adding tons of class to your vessel. Front RGB lighting is included built-in the front grille, while rear RGB lighting is an add-on with the specifically developed HTX RGB LOGO.1 accessory (available both in black and white color).



HM RGB 1 BK - Optional



HTX RGB W LOGO.1

OPTIONAL RGB LED LIGHTING REAR LOGO WHITE



HTX RGB C LOGO.1

OPTIONAL RGB LED LIGHTING REAR LOGO BLACK

The optional rear Hertz led logo creates the same sophisticated atmosphere of front led, adding tons of class to your vessel.

A	225 mm	8.86 in.
B	288 mm	11.34 in.
C	231 mm	9.09 in.
D	6 mm	0.24 in.

